







NAUTIZ X8 LEADING THE WAY

A front-runner in the new generation of handheld computers, the ergonomic Nautiz X8 delivers the largest, most brilliant capacitive touchscreen in its class, along with an unprecedented combination of processing power, connectivity and field ruggedness.

The Nautiz X8 won't just keep up with you — it'll lead the way. This dynamic handheld features a high-speed Texas Instruments 4470 dual-core 1.5 GHz processor, 1 GB of RAM, 4 GB of iNAND Flash and a 5200 mAh Li-ion battery that lasts up to 12 hours on a single charge. A choice of operating systems — Android 4.2.2 or Windows Embedded Handheld 6.5.3 — allows you to choose the most suitable platform for your needs.

Each detail of the Nautiz X8 is meticulously designed for field use, without sacrificing style or ergonomics. Its 4.7-inch high-brightness screen is the largest you'll find on any comparable computer, and you can operate the state-of-the-art capacitive touchscreen using light touch and multi-finger gestures — the same way you use your personal smart devices. The Nautiz X8's ruggedness is unparalleled. It's IP67-rated and meets stringent MIL-STD-810G U.S. military standards, which means it's impervious to both dust and water and can survive repeated drops, strong vibrations and operating temperatures ranging from -30 °C to 60 °C (-22 °F to 140 °F) — all in a sleek, attractive 490 gram (17.3 ounces) package.

The Nautiz X8 offers an exceptional combination of connectivity options and standard features, including a dedicated u-blox GPS receiver, Bluetooth 2.0 and 802.11 b/g/n WLAN functionality. A built-in 8-megapixel camera with autofocus and an LED flash lets you capture visual data quickly and easily, and connectivity through GSM/UMTS or CDMA phone data transmission keeps you connected wherever you go. Measure acceleration and orientation with the built-in G-sensor/accelerometer and gyroscope, or navigate with the integrated compass and altimeter. This handheld also features an open architecture and an extension cap system that lets you connect additional hardware such as sensors, radios and other add-ons.

The feature-rich Nautiz X8 comes ready for your team with application possibilities in forestry, public safety, field service and GIS/surveying, and it's adaptable to your work environment and performance requirements.

Carry it, wear it in a holster, toss it in your bag or mount it on your vehicle — but whatever you do, keep the rugged, reliable Nautiz X8 close at hand. You'll wonder what you ever did without it.

Österreich Latschbacher GmbH Haupstr. 8-10 A-4484 Kronstorf

Tel.: +43 (7225) 8206-0 Fax: +43 (7225) 8206- 410 e-Mail: office@winforstpro.com Deutschland Süd Latschbacher GmbH Ludwig-Zeller-Str. 44 D-83395 Freilassing Tel.: +49 (8654) 4738-0 Fax: +49 (8654) 2738-10 e-Mail: office@latschbacher.de

SiZe 190.9 mx X 92.7 mx x 34.6 mm (7.5 x 31 x 1.3 in) Weight 490 grams (17.3 ounces) (including battery and hand strap) Processor Texas Instruments 4470 dual-core @ 1.5GHz Memory/Disk 1 GB RAM4 GB INAND Flash Operating System Windows Embedded Handheld 6.5.3 Android 4.2.2 Screen 4.7" FWVGA (854x480); IPS; 600 nits, capacitive multi-touch Asahi Dragontrail chemically strengthened glass Keypad Numeric with 3 programmable function keys Battery Lion 3.7V 5200 Ah (19.2 Wh) (Warm-swappable) with smart gauge Connections USB A Host USB Micro (52 ymc and charging) DB 195.232 serial 3.5 mm headset (stereo and mic) I/O slot SM (user accessible) MicroSD/MicroSDHC slot Expansion Embe dded expansion connector for custom hardware integrations in conjunction with expansion cap. USB Host, serial, and 3.3V/Sy power connections available via proprietary connector Audio: Built in: Receiver, loud-speaker, mic Bluetooth: Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN): Voice and data, 3.3G GSM HSPA+/HSUPA or COMA EVDO Rev.A Wireless LAN: 802.11 b/g/n Navigation Integrated with stand-alone u-blox * GPS Cammera a-megapitel rear-facing camera with autofocus and tLD: Illumination </th <th></th> <th></th>		
Weight 490 grams (17.3 ounces) (including battery and hand stap) Processor Texas Instruments 4470 dual-core @ 1.5GHz Memory/Disk 1 GB RAM4 GB INAND Flash Operating System Windows Embedded Handheld 6.5.3 Android 4.2.2 Screen 4.7" FWVGA (854x480); IPS; 600 nits, capacitive multi-bouch Asahi Dragontrali chemically strengthened glass Keypad Numeric with 3 programmable function keys Battery Li-lon, 3.7V 5200 Ah (19.2 Wh) (Warm-swappable) with smart gauge Connections USB A Host USB Micro (C Sync and charging) DB 95-323 serial 3.5 mm headset (stereo and mic) I/O slot Sim (user accessible) MicroSD/MicroSDHC slot Expansion Ernbe dded expansion connector for custom hardware integrations in conjunction with expansion cap. USB Host, serial, and 3.3V/SV power connections available via proprietary connector Audio: Built in: Receiver, loud-speaker, mic Bluetooth: Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN): Voice and data, 3.3G GSM HSPA+/HSUPA or Clamera Bregapitel rearFacing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Wbration motor Sensors 3-axis a ccelerometers 3-axis a crelerometers 3-axis a crelerometers 3-axis a crelerometers 3-axis a crelerometers 3-axis a crelerometers 3-axis avis crelerometers 3-axis avis crelerometers 3-axis avis crelerometers 3-axis avis crelerometers 3-axis avis crelerometers 3-axis a	Size	190.9 mm x 79.7 mm x 34.6 mm (7.5 x 3.1 x 1.3 in)
Memory/Disk 1 GB RAM/4 GB INAND Flash Operating System Windows Embedded Handheld 6.5.3 Android 4.2.2 Screen 4.77 FWVGA (854/8480); IPS; 600 nits; capacitive multi-touch Asahi Dragontrail chemically strengthened glass Keypad Numeric with 3 programmable function keys Battery Li-lon, 3.7V 5200 Ah (19.2 Wh) (Warm-swappable) with smart gauge Connections USB A Host USB micro (PC sync and charging) DB 95:322 senial .35 mm headset (stereo and mic) I/O slot SiM (user accessible) MicroSD/MicroSDHC slot Expansion Embe dded expansion connector for custom hardware integrations in conjunction with expansion cap. USB Host, senial and 3.3V/Sv power connections available via proprietary connector Audio: Built in: Receiver, loud-speaker; mic Bluetooth: Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN): Voice and data, 3.8G GSM HSPA+/HSUPA or CDMA EVDO Rev. A Wireless LAN: 802.11 b/g/n Navigation Integrated with stand-alone u-blox * GPS Carmera B-megapixel rear-facing camera with autofocus and LED illumination Indicators LED: 1. Charge state, 2 GPS, 3. Notification; Vibration motor Sensors 3-axis a ccelerometers Proximity Arabient timperature	Weight	5
Operating System Windows Embedded Handheld 6.5.3 Android 4.2.2 Screen 4.7" FWVGA (854x480); IPS; 600 nits, capacitive multi-touch Asahi Dragontrail chemically strengthened glass Keypad Numeric with 3 programmable function keys Battery Li-lon, 3.7V 5200m Ah (19.2 Wh) (Warm-swappable) with smart gauge Connections USB A Host USB micro (PC sync and charging) DB9 R5-222 serial 3.3 mm headset (stereo and mic) I/O slot Sim (user accessible) MicroSD/MicroSDHC slot Expansion Embe dded expansion connector for custom hardware integrations in conjunction with expansion conjust the synawican connections available via proprietary connector Communication Built in: Receiver, loud-speaker, mic Bluetooth: Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN): Voice and data, 3.3G GSM HSPA+/HSUPA or CDMA EVDO Rev. A Wireless LAN: 80.211 l/g/n Navigation Integrated with stand-alone u-blox * GPS Camera B-megapixel rear-facing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Vibration motor Sensors 3-axis a ccelerometers 3-axis a ccelerometers 3-axis a ccelerometers 3-axis gyroscope Ambient temperature Environment Operating: HSD-810G S01.5/502.5 I, II and III Drop:	Processor	Texas Instruments 4470 dual-core @ 1.5GHz
Android 4.2.2 SCTEEN 4.7 FWVGA (854×480); PS; 600 nits, capacitive multi-rouch Asahi Dragontrail chemically strengthened glass Keypad Numeric with 3 programmable function keys Battery Li+on, 3.7V 5200m Ah (19.2 Wh) (Warm-swapable) with smart gauge Connections USB Airos (PC sync and charging) DB9PS.232 serial 3.5 mm headset (stereo and mic) I/O slot Sinv (user accessible) MicroSD/MicroSDCH slot Expansion Embe dded expansion connector for custom hardware integrations in conjunction with expansion cap. USB hots; regil, and 3.3v/V power connections available via proprietary connector Communication Built in: Receiver, loud-speaker; mic Bluetooth: Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN): Voice and data, 3.8G GSM HSPA+/HSUPA or COMA EVDO Rev A Wireless LAN: 802.11 b/g/n Navigation Integrated with stand-alone u-blox * GPS Carmera B-megapkel rear-facing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Vibration motor SenSOrS 3-axis gyroscope Ambient ilght sensor Digital compass Altimeter/barometer Proximity Ambient temperature Drop: 4/1.22 m; ML-STD-810G 501.5/502.5 l, II and III Drop: 4/1.22 m; ML-STD-810G 501.5/502.5 l, II and III Drop: 4/1.22 m; ML-STD-810G 501.5/502.5 l, II and III Drop:	Memory/Disk	1 GB RAM/4 GB iNAND Flash
capacitive multi-fouch Asahi Dragontrail chemically strengthened glassKeypadNumeric with 3 programmable function keysBatteryLi-Ion, 3.77 S200m Ah (19.2 Wh) (Warm-swappable) with smart gaugeConnectionsUSB A HostUSB A HostUSB A HostI/O slotUSB Micro (PC sync and charging) DB9 R5-323 serial 3.5 mm headset (stereo and mic)I/O slotSilf (User accessible) MicroSD/MicroSDHC slotExpanSionEmbe ded expansion connector for custom hardware integrations in conjunction with expansion cap. USB Host, serial, and 3.30'sv power connections available via proprietary connectorCommunicationBuilt in: Receiver, loud-speaker; micBluetooth:Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN):Vice and data, 36G GSM HSPA+/HSUPA or CDMA EVDO Rev. AWireless LAN:802.11 b/g/nNavigationIntegrated with stand-alone u-blox * GPSCarmera8-megapixel rear-facing camera with autofocus and LED illuminationIndicatorsLEDs: 1. Charge state, 2. GPS, 3. Notification; Vibration motorSenSors3-axis a ccelerometers 3-axis groycocpe Ambient light sensor Digital compass Attimeter/barometer Proximity Ambient Sol 5.5/502.5 I, II and IIIDrop:<	Operating System	
Battery Li-lon, 3.7V 5200m Ah (19, 2 Wh) (Warm-swappable) with smart gauge Connections USB A Host USB Micro (PC sync and charging) DB9 R5-323 serial 3.5 mm headset (stereo and mic) I/O slot SiM (user accessible) MicroSD/MicroSDHC slot ExpanSion Embe dded expansion connector for custom hardware integrations in conjunction with expansion cap. USB Host, serial, and 3.3v/sv power connections available via proprietary connector Communication Built in: Receiver, loud-speaker; mic Bluetooth: Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN): Voice and data, 38G GSM HSPA+/HSUPA or CDMA EVDO Rev. A Wireless LAN: 802.11 b/g/n Navigation Integrated with stand-alone u-blox * GPS Carmera &-megapixel rearfacing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Vibration motor Sensors 3-axis a ccelerometers -axis gyroscope Ambient light sensor Digital compass Attimeter/barometer Proximity MiL-STD-810G S01.5/502.51, II and III Drop: 4/1.22 m; MIL-STD-810G S01.5/502.51, II and III Drop: 4/1.22 m; MIL-STD-810G S01.5/502.51, II and III Storage : IP67, IEC 605.29 Wate: IP67, IEC 605.29 Wate: IP67, IEC 605.29 Wate: Storage : Soland & Dust : IP67, IEC 605.29 Wate:	Screen	capacitive multi-touch Asahi Dragontrail
Warm-swappable) with smart gauge Connections USB A Host USB Micro (PC sync and charging) DB9 RS-232 serial 3.5 mm headset (stereo and mic) I/O slot I/O slot SiM (user accessible) Expansion Embe dded expansion connector for custom hardware integrations in conjunction with expansion cap. USB Hots, serial, and 3.3v/Sv power connectors available via proprietary connector Communication Audie: Bluetooth: Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN): Voice and data, 3.8G (SM HSPA+/HSUPA or CDWA EVDO Rev. A Wireless LAN: 802.11 h/g/n Navigation Integrated with stand-alone u-blox * GPS Camera &-megapixel rear-facing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Wibration motor SenSOrS SenSors 3-axis groscope Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient light sensor Digital compass Altimeter/barometer Proximity Altime	Keypad	Numeric with 3 programmable function keys
USB micro (PC sync and charging) DB9 R5-232 serial 3.5 mm headset (stereo and mic) I/O slot SIM (user accessible) MicroSD/MicroSDHC slot ExpanSion Embed ded expansion connector for custom hardware integrations in conjunction with expansion cap. USB Host, serial, and 3.3v/Sv power connections available via proprietary connector Communication Audio: Biletooth: Callular (WWAN): Voice and data, 3.8G GSM HSPA+/HSUPA or CDMA EVDO Rev. A Wireless LAN: 802.11 b/g/n Navigation Integrated with stand-alone u-blox * GPS Camera 8-megapixel rear-facing camera with autofocus and LED illumination Indicators ELDS: 1. Charge state, 2. GPS, 3. Notification; Vibration motor Sensors 3-axis a ccelerometers 3-axis groscope Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient 16th 5051.5/502.5 I, II and III Storage: 4/1.22 m; MIL-STD-810G 501.5/502.5 I, II and III Drop: 4/1.22 m; MIL-STD-810.5 11.6 IV Vibration: MIL-STD-810.5 (Method 503.5, Procedure I and II, MIL-STD-810.6, Method 503.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C) MIL-STD-810.6, Method 503.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C) MIL-STD-810.6, Method 503.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C) MIL-STD-810.6, Method 503.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C) MIL-STD-810.6, Method 503.5, Procedure II		
MicroSD/MicroSDHC slot Expansion Audio: Embe dede expansion connector for custom hardware integrations in conjunction with expansion cap. USB Host, serial, and 3.3/55 power connections available via proprietary connector Communication Audio: Biletooth: Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN): Voice and data, 3.8G GSM HSPA+/HSUPA or CDMA EVDO Rev. A Wireless LAN: 802.11 b/g/n Navigation Integrated with stand-alone u-blox * GPS Camera 8-megapixel rear-facing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Wibration motor SenSors 3-axis a ccelerometers 3-axis gryoscope Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient temperature Environment Operating: -40°C to +70°C MIL-STD-810G 501.5/502.5 I, II and III Drop: -40°C to +70°C MIL-STD-810G SOD.5 I, II and III Drop: -40°C to +70°C MIL-STD-810G SOD.5 I, II and III Solar Exposure: Survives prolonged UW exposure, MIL-STD-810G, Method 503.5, Procedure I and II, Category 5 Sand & Dust : Poetice Detween -22°F and 140°F (-30°C and +60°C), MIL-STD-810G, Method 503.5, Procedure II Temperature Shock: Cycles between -22°F and 140°F (-30°C and +60°C), MIL-STD-810G, Method 503.5, Procedure II Temperature Shock: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick	Connections	USB micro (PC sync and charging) DB9 RS-232 serial
hardware integrations in conjunction with expansion cap. USB Host, serial, and 3.3v/Sv power connections available via proprietary connector Audio: Built in: Receiver, loud-speaker; mic Bluetooth: Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN): Voice and data, 3.8G GSM HSPA+/HSUPA or CDMA EVDO Rev. A Wireless LAN: 802.11 b/g/n Navigation Integrated with stand-alone u-blox * GPS Camera 8-megapixel rear-facing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Vibration motor SenSors 3-axis a ccelerometers 3-axis gyroscope Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient Temperature Environment Operating: -30° C to + 60 °C MIL-STD-810G 501.5/502.5 I, II and III Storage: -30° C to + 60 °C MIL-STD-810G 501.5/502.5 I, II and III Drop: 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G 507.5/502.5 I, II and III Drop: 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G 507.5/502.5 I, II and III Drop: 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G 507.5/502.5 I, II and III Storage : IP67, IEC 60529 Humidity: 09% relative at -30° C to +60 °C; MIL-STD-810G 507.5 II Altitude: Storage Stribertor 106 505.5 J, II and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure I and II, Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G , Method 505.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C), MIL-STD-810G , Method 505.5, Procedure I. Coptional: Tall expansion cap, Screen protector	I/O slot	· · · · · · · · · · · · · · · · · · ·
Audio: Built in: Receiver, loud-speaker; mic Bluetooth: Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN): Voice and data, 3.8G GSM HSPA+/HSUPA or CDMA EVDO Rev. A Wireless LAN: 802.11 b/g/n Navigation Integrated with stand-alone u-blox * GPS Camera 8-megapixel rear-facing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Vibration motor Sensors 3-axis a ccelerometers 3-axis gyroscope Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient temperature Environment Operating: - 30° C to + 60° C MIL-STD-810G 501.5/502.5 I, II and III Drop: -40° C to + 70° C MIL-STD-810G 501.5/502.5 I, II and III Drop: 4/1.122 m; MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G, Method 514.6, Procedure I and II, Category 5 Sand & Dust : IP67, IEC 60529 Water: IP67, IEC 60529 Water: IP67, IEC 60529 Water: Ip5,000/4,500+ m; MIL-STD-810G 500.5 I, II and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G 505.5, Procedure I MIL-STD-810G, Method 505.5, Procedure I MIL-STD-810G, Method 503.5, Procedure I.C	Expansion	hardware integrations in conjunction with expansion cap. USB Host, serial, and 3.3v/5v power
Bluetooth: Class 2 (10 m), v3.0 in Android OS and v2.0 in Windows Mobile OS Cellular (WWAN): Voice and data, 3.8G GSM HSPA+/HSUPA or CDMA EVDO Rev. A Wireless LAN: 802.11 b/g/n Navigation Integrated with stand-alone u-blox * GPS Carmera & megapixel rear-facing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Vibration motor Sensors 3-axis a ccelerometers 3-axis gyroscope Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient temperature Environment Operating: -30°C to + 60°C MIL-STD-810G 501.5/502.5 I, II and III Storage : -40°C to +70°C MIL-STD-810G 501.5/502.5 I, II and III Drop: 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G 515.60.8 Vibration: MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G 516.6 IV MIL-STD-810G 507.5 II Altitude: IP67, IEC 60529 Water: IP67, IEC 60529 Mater: Survives prolonged UVB exposure, MIL-STD-810G, Method 514.6, Procedure I and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G 507.5 II Altitude: Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C), MIL-STD-810G, Method 503.5, Procedure I. Temperature Shock: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector		
Cellular (WWAN): Voice and data, 3.8G GSM HSPA+/HSUPA or CDMA EVDO Rev. A Wireless LAN: 802.11 b/g/n Navigation Integrated with stand-alone u-blox * GPS Camera 8-megapixel rear-facing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Vibration motor Sensors 3-axis a ccelerometers 3-axis gyroscope Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient temperature ML-STD-810G 501.5/502.5 l, ll and lll Storage : -40° C to + 70° C MIL-STD-810G 501.5/502.5 l, ll and lll Storage : Drop: 4/1.22 m; MIL-STD-810G 501.6.6 lV Vibration: MIL-STD-810G 501.5/502.5 l, ll and lll Drop: 4/1.22 m; MIL-STD-810G 50.6.6 lV Vibration: MIL-STD-810G 501.5/502.5 l, ll and lll Drop: 4/1.22 m; MIL-STD-810G 50.5.6 lV Wibration: IP67, IEC 60529 Mater: IP67, IEC 60529 Mundity: 90% relative at -30°C to +60°C; MIL-STD-810G, Method 503.5, Procedure l and lll Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 503.5, Procedure l-C Options SkUs:		
Navigation Integrated with stand-alone u-blox * GPS Camera & megapixel rear-facing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Wibration motor Sensors 3-axis a ccelerometers 3-axis gyroscope Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient temperature Environment • 0° C to + 60° C MIL-STD-810G 501.5/502.5 I, II and III Storage : -40° C to + 70° C MIL-STD-810G 501.5/502.5 I, II and III Drop: 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G 501.5/502.5 I, II and III Drop: 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G, Method 514.6, Procedure I and II, Category 5 Sand & Dust : IP67, IEC 60529 Water: IP67, IEC 60529 Water: IP67, IEC 60529 Mul-STD-810G 507.5 II Altitude: 15,000/4,500+ m; MIL-STD-810G 500.5 I, II and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C), MIL-STD-810G, Method 503.5, Procedure II Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 503.5, Procedure II Temperature Shock:	Cellular (WWAN):	Voice and data, 3.8G GSM HSPA+/HSUPA or
Camera &-megapixel rear-facing camera with autofocus and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Vibration motor Sensors 3-axis a ccelerometers 3-axis gyroscope Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient temperature Environment Operating: Operating: -30° C to + 60° C MIL-STD-810G 501.5/502.5 I, II and III Storage : -40° C to + 70° C MIL-STD-810G 501.5/502.5 I, II and III Drop: 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G, bethod 514.6, Procedure I and II, Category 5 Sand & Dust : IP67, IEC 60529 Water: IP67, IEC 60529 Humidity: 90% relative at -30°C to +60°C; MIL-STD-810G 507.5 II Altitude: 15,000//4,500+ m; MIL-STD-810G 500.5 I, II and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure II Temperature Shock: Cycles between -22°F and 140°F (-30°C and +60°C), MIL-STD-810G , Method 503.5, Procedure I-C Options SkUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector	Wireless LAN:	802.11 b/g/n
and LED illumination Indicators LEDs: 1. Charge state, 2. GPS, 3. Notification; Vibration motor Sensors 3-axis gyroscope Ambient light sensor Digital compass Attimeter/barometer Proximity Ambient temperature Environment Operating: - 30° C to + 60°C MIL-STD-810G 501.5/502.5 I, II and III Storage: - 40° C to + 70°C MIL-STD-810G 501.5/502.5 I, II and III Drop: - 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: - MIL-STD-810G 511.5/502.5 I, II and III Drop: - 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: - MIL-STD-810G 501.5/502.5 I, II and III Drop: - 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: - MIL-STD-810G 501.5/502.5 I, II and III Drop: - 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: - MIL-STD-810G 501.5/502.5 I, II and III Drop: - 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: - MIL-STD-810G 507.5 II Attitude: - 1P67, IEC 60529 Water: - 1P67, IEC 60	Navigation	Integrated with stand-alone u-blox [®] GPS
Vibration motor Sensors 3-axis a ccelerometers 3-axis gyroscope Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient temperature Environment Operating: - 30° C to + 60° C MIL-STD-810G 501.5/502.5 I, II and III Storage : - 40° C to + 70° C MIL-STD-810G 501.5/502.5 I, II and III Drop: 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G, Method 514.6, Procedure I and II, Category 5 Sand & Dust : IP67, IEC 60529 Water: IP67, IEC 60529 Water: IP67, IEC 60529 Humidity: 90% relative at -30°C to +60°C; MIL-STD-810G, Method 505.5, Procedure I and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure II Temperature Shock: Cycles between -22°F and 140°F (-30°C and +60°C), MIL-STD-810G , Method 503.5, Procedure I-C Options SKUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector		
3-axis gyroscope Ambient light sensor Digital compass Altimeter/barometer Proximity Ambient temperature Environment Operating: -30°C to + 60°C MIL-STD-810G 501.5/502.5 l, ll and lll Storage : -40°C to + 70°C MIL-STD-810G 501.5/502.5 l, ll and lll Drop: 4/1.22 m; MIL-STD-810G 516.6 IV Vibration: MIL-STD-810G, Method 514.6, Procedure I and ll, Category 5 Sand & Dust : IP67, IEC 60529 Water: IP67, IEC 60529 Water: IP67, IEC 60529 Water: IP67, IEC 60529 Water: IP67, IEC 60529 Mul-STD-810G 507.5 II Altitude: 15,000/4,500+ m; MIL-STD-810G 500.5 I, II and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 503.5, Procedure I MIL-STD-810G, Method 503.5, Procedure II Temperature Shock: Cycles between -22°F and 140°F (-30°C and +60°C), MIL-STD-810G of Method 503.5, Procedure I-C Options StUs: SKUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus,	Indicators	-
EnvironmentOperating: -30° C to $+60^{\circ}$ C MIL-STD-810G 501.5/502.5 I, II and IIIStorage : -40° C to $+70^{\circ}$ C MIL-STD-810G 501.5/502.5 I, II and IIIDrop : $4'/1.22$ m; MIL-STD-810G 516.6 IVVibration :MIL-STD-810G, Method 514.6, Procedure I and II, Category 5Sand & Dust :IP67, IEC 60529Water:IP67, IEC 60529Humidity:90% relative at -30°C to +60°C; MIL-STD-810G 507.5 IIAltitude:15,000/4,500+ m; MIL-STD-810G 500.5 I, II and IIISolar Exposure:Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure ITemperature Shock:Cycles between -22°F and 140°F (-30°C and +60°C), MIL-STD-810G , Method 503.5, Procedure I-COptions SKUs:Verizon CDMA, GSM Included in box:Included in box:International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guideOptional:Tall expansion cap, Screen protector	Sensors	3-axis gyroscope Ambient light sensor Digital compass Altimeter/barometer Proximity
MIL-STD-810G 501.5/502.5 I, II and III Storage : -40 ° C to + 70 °C MIL-STD-810G 501.5/502.5 I, II and III Drop : 4/1.22 m; MIL-STD-810G 516.6 IV Vibration : MIL-STD-810G, Method 514.6, Procedure I and II, Category 5 Sand & Dust : IP67, IEC 60529 Water: IP67, IEC 60529 Humidity: 90% relative at -30°C to +60 °C; MIL-STD-810G 507.5 II Altitude: 15,000/4,500+ m; MIL-STD-810G 500.5 I, II and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure I Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C), MIL-STD-810G , Method 503.5, Procedure II Options SKUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector	Environment	
Storage : $-40 \degree C$ to $+70 \degree C$ MIL-STD-810G 501.5/502.5 l, ll and llDrop : $4'/1.22 m$; MIL-STD-810G 516.6 lVVibration :MIL-STD-810G, Method 514.6, Procedure I and II, Category 5Sand & Dust :IP67, IEC 60529Water :IP67, IEC 60529Humidity:90% relative at -30°C to +60°C; MIL-STD-810G 507.5 llAltitude:15,000/4,500+ m; MIL-STD-810G 500.5 l, ll and IIISolar Exposure:Survives prolonged UVB exposure, MIL-STD-810G 505.5, Procedure ITemperature Shock:Cycles between -22 °F and 140 °F (-30°C and +60°C), MIL-STD-810G , Method 503.5, Procedure ICOptions SKUs:Verizon CDMA, GSM Included in box:Included in box:International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guideOptional:Tall expansion cap, Screen protector	Operating:	
Drop:4'/1.22 m; MIL-STD-810G 516.6 IVVibration:MIL-STD-810G, Method 514.6, Procedure I and II, Category 5Sand & Dust :IP67, IEC 60529Water:IP67, IEC 60529Humidity:90% relative at -30°C to +60°C; MIL-STD-810G 507.5 IIAltitude:15,000'/4,500+ m; MIL-STD-810G 500.5 I, II and IIISolar Exposure:Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure IITemperature Shock:Cycles between -22 °F and 140 °F (-30°C cand +60°C), MIL-STD-810G , Method 503.5, Procedure I-COptions SKUs:Verizon CDMA, GSM Included in box:Included in box:International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guideOptional:Tall expansion cap, Screen protector	Storage :	- 40 ° C to + 70 °C
Vibration: MIL-STD-810G, Method 514.6, Procedure I and II, Category 5 Sand & Dust : IP67, IEC 60529 Water: IP67, IEC 60529 Humidity: 90% relative at -30°C to +60°C; MIL-STD-810G 507.5 II Altitude: 15,000/4,500+ m; MIL-STD-810G 500.5 I, II and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C), MIL-STD-810G , Method 503.5, Procedure I-C Options SKUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector	Drop	,
Sand & Dust : IP67, IEC 60529 Water: IP67, IEC 60529 Humidity: 90% relative at -30°C to +60°C; MIL-STD-810G 507.5 II Altitude: 15,000/4,500+ m; MIL-STD-810G 500.5 I, II and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C), MIL-STD-810 G , Method 503.5, Procedure I-C Options SKUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector	'	MIL-STD-810G, Method 514.6, Procedure I and II,
Water: IP67, IEC 60529 Humidity: 90% relative at -30°C to +60°C; MIL-STD-810G 507.5 II Altitude: 15,000/4,500+ m; MIL-STD-810G 500.5 I, II and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C), MIL-STD-810 G, Method 503.5, Procedure I-C Options SKUs: SKUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector	Sand & Dust	
MIL-STD-810G 507.5 II Altitude: 15,000'/4,500+ m; MIL-STD-810G 500.5 I, II and III Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30 °C and +60 °C), MIL-STD-810G, Method 503.5, Procedure I-C Options SKUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector Deutschland Nord Schweiz		
Solar Exposure: Survives prolonged UVB exposure, MIL-STD-810G, Method 505.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C), MIL-STD-810G , Method 503.5, Procedure I-C Options SKUs: Verizon CDMA, GSM Included in box: Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector	Humidity:	
MIL-STD-810G, Method 505.5, Procedure II Temperature Shock: Cycles between -22 °F and 140 °F (-30°C and +60°C), MIL-STD-810G, Method 503.5, Procedure I-C Options SKUs: SKUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector Deutschland Nord Schweiz		
(-30°C and +60°C), MIL-STD-810G , Method 503.5, Procedure I-C Options SKUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector Deutschland Nord Schweiz	solar Exposure:	MIL-STD-810G, Method 505.5, Procedure II
Options SKUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector	Temperature Shock:	(-30°C and +60°C),
SKUs: Verizon CDMA, GSM Included in box: International pow er adapter, Capacitive stylus, Battery, Hand strap, 3.5 mm headset, USB cable, Quick-start guide Optional: Tall expansion cap, Screen protector	Options	
Quick-start guide Optional: Tall expansion cap, Screen protector Deutschland Nord Schweiz	SKUs:	International pow er adapter, Capacitive stylus,
Deutschland Nord Schweiz	Optional:	Quick-start guide
Ables ITS Latschbacher AG Benzstraße 5 Ouarzwerkstrasse 17	Abies ITS	Latschbacher AG

Abies ITS Benzstraße 5 D-37083 Göttingen Tel.: +49 (551) 49803-11 Fax: +49 (551) 49803-29 e-Mail: office@abies.de Schweiz Latschbacher AG Quarzwerkstrasse 17 CH-8463 Benken ZH Tel.: +41 (52) 315 2357 Fax: +41 (52) 315 2358 e-Mail: office@latschbacher.ch

LATSCHBACHER